

Datasheet revision 1.4 www.chipquik.com

Multi-Purpose Silicone Grease (Clear) 10.2oz Cartridge

Product Highlights

Multi-Purpose Silicone Grease Insulates Electronic Components Water and Moisture Resistant Lubricates and Seals Parts Excellent Dielectric Grease Latex Free (Silicone-Based Grease, Does Not Contain Latex) Non-Curing



Common Uses

Lubricating and Sealing. Dielectric Grease.

Instructions

Surfaces should be clean and dry. For detached nozzle cartridge, cut the tip off of the cartridge just above the nozzle threads. Thread nozzle onto cartridge and cut the tip off of the nozzle to the required bead size. Dispense by pushing the silicone grease in the direction of the nozzle with a cartridge dispensing gun. Tool or form the silicone grease as per application requirements. Apply the silicone to surfaces and remove the excess silicone after tooling with a dry clean cloth.

Specifications

Meets and Exceeds: SAE-AS-8660

VOC:
Operating Temperature Range:
Curing Time:

VOC Compliant (<3%), Low Odor
-57°C to +204°C (-70°F to +400°F)
Non-Curing Grease, Retains Consistency

Color: Clear

Dielectric Strength: 460 V/mil (18 kV/mm)

Latex Free: Yes, Silicone-Based Grease, Does Not Contain Latex

Size: 10.2oz Cartridge

Storage and Handling

Store refrigerated or at room temperature 3-25°C (37-77°F).

Shelf Life

>60 months

Transportation

This product has no shipping restrictions. Shipping below 0°C (32°F) or above 25°C (77°F) for normal transit times by ground or air will not impact this product's stated shelf life.